



TYRE CATALOGUE





CEAT KELANI Holdings is a successful joint venture between **CEAT India** and **Kelani Tyres Sri Lanka**, solidifying our commitment to delivering exceptional tyre solutions to international markets. Under the banner of CEAT KELANI Holdings, our key brand, **CEAT**, has been meticulously crafted to conquer the diverse terrains of the global market.

As the leading tyre manufacturer in Sri Lanka, we specialize in the production of top-tier pneumatic cross-ply tyres designed to meet the demands of heavy commercial vehicles, light commercial vehicles and agricultural equipment (farm tyres). Additionally, we manufacture radial construction tyres tailored for heavy and light commercial vehicles, passenger cars, vans and SUVs. Our portfolio also includes two-wheeler and three-wheeler tyres, complemented by the marketing of tubes and flaps (rim-tape), all of which uphold our unwavering commitment to providing products of the highest quality, characterized by durability and comfort.

Our pledge to uphold the highest standards is backed by prestigious certifications, including the IATF 16949 awarded by the International Automotive Task Force and ISO 9001:2015, ensuring that our offerings meet and surpass global expectations.

CEAT KELANI Holdings proudly commands a leading position in the Sri Lankan tyre market, boasting over 50% market share. Beyond our national borders, our esteemed brand ORION has established a formidable presence in more than 15 countries worldwide.

Our tyre manufacturing process is driven by ownership of two of Sri Lanka's largest tyre manufacturing facilities, equipped with cutting-edge technology. This technological edge empowers CEAT KELANI Holdings to consistently produce tyres that meet stringent global standards. Our tyre products adhere to international certifications such as E-mark (e4), SNI and BIS, underlining our unwavering commitment to quality.

These achievements represent just a snapshot of our ongoing pursuit of superior quality. As we continue to push boundaries, we invite you to experience the excellence that defines CEAT KELANI Holdings and the ORION brand, your trusted tyre partner on the global stage.



**CRAFTED WITH
CUTTING EDGE
GERMAN TECHNOLOGY**





BETTER HANDLING
 //



QUIETER RIDE
 //



FUEL EFFICIENT
 //



LOW VIBRATION
 //



BETTER CONTACT
 //



FUELSMARRT

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
155/80R12	4	77T	TL	4.5x12	550	159	7.5
145/80R12	4	74T	TL	4.0x12	535	145	7.5
145/70R12	4	69T	TL	4.0x12	510	155	7.3
185/70R13	4	86T	TL	5.5x13	591.8	187	8.6
175/70R13	4	82T	TL	5.0x13	576	177	7.9
165/80R13	4	83T	TL	4.5x13	592	166	7.5
165/65R13	4	77T	TL	5.0x13	544	170	7.5
155/80R13	4	79T	TL	4.5x13	579	153	8.3
155/65R13	4	73T	TL	4.5x13	533	154	7.5
185/70R14	4	88H	TL	5.5x14	617	190	7.3
185/65R14	4	86T	TL	5.5x14	592	186	7.8
175/70R14	4	84H	TL	5.1x14	496	175	7.3
175/65R14	4	82H	TL	5.0x14	582	176	7.5
165/70R14	4	81T	TL	5.0x14	588	170	7.7
165/55R14	4	72T	TL	5.0x14	537	161	6.6
155/65R14	4	75T	TL	4.5x14	558	155	7.2
185/60R15	4	88H	TL	5.5x15	605.8	187	7.3

**CRAFTED WITH
CUTTING EDGE
GERMAN TECHNOLOGY**




BETTER HANDLING

LOW NOISE

HIGHER MILEAGE

BETTER AQUA PLANING

**EFFECTIVE BRAKING
ON WET SURFACE**


SECURA DRIVE

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
195/65R15	4	91H	TL	6.0x15	637	197	8.01
185/65R15	4	88H	TL	5.5x15	620	185	7.4
175/65R15	4	88H	TL	5.0x15	610	175	7.7
165/55R15	4	75H	TL	5.0x15	564	166	7.5
205/60R16	4	92H	TL	6.0x16	621	205	8.0
205/55R16	4	94H	TL	6.5x16	632	210	7.8
185/55R16	4	83H	TL	6.0x16	610	192	8.2
215/55R17	4	94V	TL	7.0x17	666	224	8.2

**CRAFTED WITH
CUTTING EDGE
GERMAN TECHNOLOGY**



**BETTER HANDLING****BETTER AQUAPLANING****BETTER WET GRIP****NO VIBRATION****BETTER CONTACT**

CZAR

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)	PATTERN
205/75R14	8	98S	TL	6.0x14	665	212	7.8	HT
31.00-10.5R 15	8	109S	TL	8.5x15	776	274	12.5	AT
255/70R15	8	108T	TL	7.5x15	739	260	9.0	AT
235/75R15	8	105S	TL	6.5x15	733	234	10.3	AT
215/75R15	8	100S	TL	6.0x15	702	218	10.5	AT
205/75R15	8	99S	TL	6.0x15	692	215	8.5	HP
265/70R16	8	112S	TL	8.0x16	780	266	9.5	HP
235/70R16	8	106T	TL	7.0x16	733	234	10.3	AT
205R16	8	110/108S	TL	5.5x16	736	203	10.4	AT
225/60R17	8	99H	TL	7.0x17	702	228	8.3	HP





4 RIB HIGHLAND DESIGN
 //////////////////////////////////



DURABILITY
 //////////////////////////////////



CAR RADIAL/LIGHT COMMERCIAL

MILAZE

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
135/70R12	4	65S	TL	4.0x12	496	145	7



**ENHANCED GRIP
AND UNIFORM WEAR**
 //////////////////////////////////



NO CUTTING OR CHIPPING
 //////////////////////////////////



BETTER HEAT DISSIPATION
 //////////////////////////////////



BETTER TYRE LIFE & DURABILITY
 //////////////////////////////////



MILAZE HD

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
215/75R15	8	115/113S	TL	6.0x15	703	215	9.8





ZIG-ZAG CIRCUMFERENTIAL RIBS



DURABILITY



NO CUTTING OR CHIPPING



VAN RADIAL

RHINO PLUS

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)	PATTERN
155R12	8	88/86Q	TL	4.5x12	555	154	7.8	RHINO PLUS
155R12	8	88/86Q	TL	4.5x12	560	160	8.3	SUPER RHINO PLUS
155R13	8	90/89R	TL	4.5x13	579	150	8.3	RHINO PLUS
165R13	8	94/92R	TL	4.5x13	599	167	8.9	RHINO PLUS
165R14	8	97/95Q	TL	4.5x14	624	165	8.8	RHINO PLUS
185R14	8	102/100R	TL	5.5x14	653	193	9.4	RHINO PLUS
195R14	8	106/104R	TL	5.5x14	670	198	9.6	RHINO PLUS
195R14	8	106/104R	TL	5.5x14	672	201	8.5	SUPER RHINO PLUS
195R15	8	106/104R	TL	5.5x15	691	196	10.1	RHINO PLUS





**EXCELLENT STEERABILITY
WITH UNIFORM WEAR**



RETREADABILITY



ROBUST CARCASS



OPTIMIZED SHOULDER RIB DESIGN



LIGHT TRUCK

F.M.SLEEK

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
6.50-14	8	102/100 L	TT	4.5X14	700	182	10.3
6.50-14	10	105/103 L	TT	4.5X14	700	182	10.3
6.50-16	10	102/98 L	TT	4.5X16	768	180	10.6
7.00-15	10	-	TT	5.5X15	763	202	11.8
7.00-15	12	114/109 L	TT	5.5X15	763	202	11.8
7.50-15	12	119/115 L	TT	6.0X15	754	215	12.5
7.50-16	12	120/116 L	TT	6.0X16	810	215	11.5
7.00-16	10	-	TT	5.5X15	782	200	11.6
7.00-16	12	115/110 L	TT	5.5X16	787	201	12.6
7.50-16	14	122/118 L	TT	6.0X16	810	215	11.5
7.50-16	16	123/129 L	TT	6.0X16	812	218	12.8



**SPECIAL 4 RIB PATTERN****SEMI STEEL CONSTRUCTION****SOLID SHOULDER NOTCHES**

RADIAL PLUS

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.00R16	12	117/116N	TL	5.5x16	778	202	10.5
7.50R16	12	121/120M	TT	6.0x16	803	202	11.0

**CIRCUMFERENTIAL BUTTRESS DESIGN****NEW CAVITY DESIGN****SPECIALLY DEVELOPED COMPOUND IN BEAD**

MILAZE HD

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.00R15	10	110/105N	TL	5.5x15	751	211	11.3



**HIGH MILEAGE**

////////////////////

**SUPERIOR RETREADABILITY**

////////////////////

**ROBUST CARCASS**

////////////////////

**VENTILATED AND
RE-INFORCED BUTTRESS**

////////////////////



LUG PLUS

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.50-16	16	123/119L	TT	6.0x16	825	220	17.5

**SELF COOLING
BUTTRESS COUTOUR**

////////////////////

**ELIMINATION OF STONE
TRAPPING & SUPERIOR GRIP**

////////////////////

**ENRICHED DURABILITY**

////////////////////

**ROBUST LUG DESIGN**

////////////////////



EXTRA GRIP

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
6.00-16	6	95/93L	TT	4.5x16	682	170	9.5



**ENRICHED DURABILITY**

//////////

**BEST RETREADABILITY**

//////////

**ROBUST CARCASS**

//////////

**SELF COOLING
BUTTRESS COUNTOUR**

//////////



XL SUPER

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
8.25-20	14	135/130K	TT	6.5x20	992	240	13.9
9.00-20	16	141/136K	TT	7.0x20	240	272	15.5
10.00-20	16	145/141K	TT	7.5x20	13.9	278	16.5

**INNOVATED CARCASS TO
WITHSTAND MULTIPLE LIFE**

//////////

**REINFORCED KERB RIB DESIGN**

//////////

**EXTRA PROTECTION FROM
SIDEWALL DAMAGES**

//////////



XL #1

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
10.00-20	16	145/141K	TT	7.5x20	1070	281	16.5




STEERING STABILITY

HIGH MILEAGE

RETREADABILITY

DURABILITY

EXCELLENT TRACTION


WINMILE AW

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
10.00 R 20	16	146/143K	TT	7.5X20	1057	277	17.20







ZIG-ZAG GROOVE AND SIPES



BETTER MILEAGE



**EXTRA TRACTION
WITH UNIFORM WEAR**



**EXCELLENT BELT
DURABILITY**



HIGHER LOADABILITY



BRAWO ORION

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
10.00R20	16	146/143K	TT	7.5X20	1051	276	15.0



ZIG-ZAG GROOVE AND SIPES



**GROOVE BASE PROTECTOR
IN CENTER AND SHOULDER**



**HIGH ABRASION RESISTANCE
TREAD COMPOUND**



**HIGH BONDING
BELT COMPOUND**



**COOLER TREAD COMPOUND
WITH OPTIMIZED TREAD DESIGN**

WINMILE X3-AW



SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
295/80R22.5	18	154/149K	TL	9X22.5	1054	301	16.1





OPTIMIZED CARBON COMPOUND



MILEAGE EFFICIENCY



UPGRADED CORD STRENGTH



RETREADABILITY



CL-T

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
9.00-20	16	141/136K	TT	7.0x20	1045	259	20.7



**STURDY COMPOUND WITH
STRONG TURN UP AREA**



PROVIDES LONG TYRE LIFE



TOUGH NYLON CASING



CL TROLLA

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
10.00-20	16	145/141K	TT	7.5x20	1079	279	20.6
10.00-20	18	146/142K	TT	7.5x20	1079	279	20.6



**STRAIGHT LUG DESIGN**

//////////

**ELIMINATION OF
STONE TRAPPING**

//////////

**CONTINUOUS
CENTRE RIB DESIGN**

//////////

**UNIFORM TYRE WEAR**

//////////



HT 92

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
9.00-20	16	141/136K	TT	7.0x20	1053	269	20.5

**SELF COOLING
BUTTRESS COUNTOUR**

//////////

**ENRICHED DURABILITY**

//////////

**ROBUST CARCASS**

//////////

**BEST RETREADABILITY**

//////////



L 40

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
10.00-20	16	145/141K	TT	7.5x20	1076	278	19.9





**OPTIMIZED
SHOULDER RIB DESIGN**



**EXCELLENT STEERABILITY
WITH UNIFORM WEAR**



ROBUST CARCASS



**EXCELLENT
ROAD TRACTION**



BRAWO SL 999

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.50-16	16	124/120K	TT	6.0x16	830	215	14.5
8.25-16	16	129/127K	TT	6.5x16	854	234	16.0
10.00-20	16	146/142J	TT	7.5x20	1083	283	20.2





**SELF COOLING
BUTTRESS COUNTOUR**



ENRICHED DURABILITY



ROBUST CARCASS



BETTER RETREADABILITY



BRAWO SL 777

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.50-16	16	124/120K	TT	6.0x16	835	215	17.5
8.25-16	16	129/127K	TT	6.5x16	863	234	19.5
10.00-20	16	146/142J	TT	7.5x20	1085	275	21.5



**HIGH MILEAGE****SUPERIOR RETREADABILITY****ROBUST CARCASS****VENTILATED AND
RE-INFORCED BUTTRESS**

BRAWO SL LUG +

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.50-16	16	124/120K	TT	6.0x16	835	216	17.5
8.25-16	16	129/127K	TT	6.5x16	863	234	19.5
10.00-20	16	146/142J	TT	7.5x20	1085	280	24.2





**STURDY COMPOUND WITH
STRONG TURN UP AREA**



PROVIDES LONG TYRE LIFE



TOUGH NYLON CASING



BETTER CASING VALUE



CALIBER R676

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.50-16	14	122/118K	TT	6.0x16	810	210	11.2
10.00-20	16	146/142J	TT	7.5x20	1072	280	16.5





STRAIGHT LUG DESIGN



**ELIMINATION OF
STONE TRAPPING**



**CONTINUOUS
CENTRE RIB DESIGN**



UNIFORM TYRE WEAR



BRAVO S878

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.50-16	14	122/118K	TT	6.0x16	824	215	17.5
10.00-20	16	146/142J	TT	7.5x20	1085	275	21.0





SPECIAL TREAD COMPOUND



MAXIMUM LOADABILITY



HIGH MILEAGE



STRONG BEAD



PRIMERO L235

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
7.50-16	14	122/118K	TT	6.0x16	824	215	17.5
10.00-20	16	146/142J	TT	7.5x20	1080	285	20.4





**STURDY COMPOUND WITH
STRONG TURN UP AREA**



PROVIDES LONG TYRE LIFE



TOUGH NYLON CASING



BETTER CASING VALUE



HCL SUPER

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
11.00-20	18	149/144K	TT	7.5x20	1100	300	22.0
12.00-20	18	153/149K	TT	7.5x20	1134	317	23.0





**SELF COOLING
BUTTRESS COUNTOUR**



ENRICHED DURABILITY



ROBUST CARCASS



BEST RETREADABILITY



STL 888

SIZE	PR	LSI	TYPE	RIM SIZE	OD (mm)	SW (mm)	NSD (mm)
10.00-20	12	140/135K	TT	7.5x20	1050	276	9.5
10.00-20	14	144/139K	TT	7.5x20	1050	276	9.5
11.00-22.5	12	140/135K	TL	8.25x22.5	1055	275	9.5
11.00-22.5	14	144/139K	TL	8.25x22.5	1058	278	9.5



CEAT



+94 71 873 9299



damith@ceatsrilanka.com